Lyn-OUT · Outdoor fixed

High-brightness, weather-sealed cabinets for billboards and facades.



OVERVIEW

Built to stay readable in direct sun and to run through rain and dust. The energy-saving drive keeps running cost down, and right-angle joins allow corner screens for 3D content.

HIGHLIGHTS

- Up to 10,000 nits for direct sunlight
- IP66 sealed front and rear
- Energy-saving drive, maximum 680 W per square metre
- Front or rear service
- Right-angle joins for 3D corner screens

WHERE IT FITS

- Billboards
- Building facades
- Roadside advertising
- 3D corner screens

MODELS

Lyn-OUT-6.7 | Lyn-OUT-8.0 | Lyn-OUT-10.0

SPECIFICATIONS

Technology	SMD
Environment	Outdoor
Pixel pitch	6.7, 8, 10 mm
Cabinet size	960 x 960 x 78 mm, 960 x 1280 x 78 mm
Weight	28 kg per cabinet
Brightness	7,500 to 10,000 nits
Refresh rate	7,680 Hz
Protection	IP66
Service access	Front and rear
Curving	90-degree corner joins for 3D corner screens

Specifications are indicative and may change without notice. Confirm against the current datasheet before ordering. Product images are illustrations. Model names give the nominal pixel pitch in millimetres. © Lynkeus